Suppo	Job Role: Assistant Support opencast mines								
Sr. No.	NOS Code	PC Code	Question	Option A	Option B	Option C	Option D	Answer (A/B/C/D)	Difficulty Level (Easy/ Medium/ Hard)
1.	MIN/ N0239	PC1	WHILE ASSISTING PRE OPERATION CHECK THEN	OBSERVE CRACKS & DAMAGE OF BODY	FUEL LEVEL	WATER LEVEL	LUBRICANT LEVEL	ALL ABC ARE CORRECT	EASSY
2.		PC1	IF OBSERVE ANY LEAKAGES FROM HOSES THEN	INFORM SUPERVISOR	INFORM MECH.FITTER	INFORM OPERATOR	NONE OA ABC	ALLABC ARE CORRECT	EASSY
3.		PC2	PRE OPERATION CHECKS INCULUDES	WATER LEVEL	HYDRAULIC OIL LEVEL	FUEL LEVEL	ALL ARE ABC IS CORRECT	ALL ARE ABC ARE CORRECT	MEDIUM
4		PC2	TOOTH POINTS AND LOCK PINS ALSO CHECK DURING	PRE OPERATION	AFTER START	MID SHIFT INSPECTION	CONSTANT WATCH	PRE OPERATION	MEDIUM
5		PC3	WHAT ARE THE DANGER ASSOCIATED WITH THE LEAKAGES OF OIL IN MACHINE	LOSS OF OIL	INCREASE COST	FIRE	NONE OF ABC	FIRE	MEDIUM
			EVERY CRAWLER MOU NTED MACHINE SHOULD BE CHECKS						
6		PC4	FOR What factors	CHAIN PAD	BOLTS HORN	LINKS	ALL ARE ABC	ALL ARE ABC	EASSY
7		PC5	monitors in side the cabin in loader	Seat belt	,BACKUPALARM,MIRRO R	HEAD LIGHTS	GAUGES,INDICATOR S	SWITCHES,CON TROLS	
8		PC5	WHAT IS THE DUTY OF ASSIST.SUPPORT IF ANY ALARM MASSAGE HEARING IN THE CABIN	STOP THE WORK &INFORM TECHNICIAN	CARRY OUT WORK AS USUAL	WORK FAST AND LEAVE MACHINE	ALL ABC ARE CORRECT	SOT	

19	PC15	HOW TO INFLATE TIRES IN MINING AREA	UNDER THE CAG SAFETY	NORMALLY	IN SEPRATE ROOM	NONE OF ABC	UNDER THE CAG SAFETY	HARD
18	PC14	FOR CHANGING OF OIL OR FILTER WHAT PRCEEDURE FOLLOWED	MANUFRACTUR ER MANNUAL	CHANGE AS PER OUR MIND	AS PER OPERATOR	NONE OF ABC	MANUFRACTUR ER MANNUAL	HARD
17	PC13	GREASING &LUBRICATION IS NESSASSARY FOR	MOVING PARTS OF MACHINES	FRAME OF MACHINES	BOOM SAFETY	NONE OFABC	MOVING PARTS OF MACHINES	HARD
16	PC12	IF YOU WANT TO LIFT ANY PART/AXLE OF MACHINE THEN USE	POWER JAK	SPPANNER	SLIDE WRINCH	NONE OF ABC	POWER JAK	HARD
15	PC11	WHILE INSPECTING EXCAVATOR BUCKET TEEETH FOUND DAMAGED THEN	STOP MACHINE	CHANGE TEETH	вотн а&в	NONE OF ABC	BOTH A&B	EASSY
14	PC11	DAMPER WHILE RUNNING OBSERVE LEAKAGE THEN	INFORM OPERATION	REPORT TO FITTER	WRITE IN REPORT	NONE OF ABOVE	INFORM OPERATOR	EASSY
13	PC1 0	NO REPAIR /MAINTENANCE WORK IS PERFORMED ON HEMM BEFORE	ENGINE IS STOPED	ENGINE TEMPERATURE COOLDOWN	LOCKOUT /TUGOUT PROPERLY	ALLABC ARE CORRECT	ALL ABC ARE CORRECT	MEDIUM
12	PC9	ASIST.SUPPORT SHOULD FOLLOW THE ORDER OF	MANAGER	INCHARGE FITTER/TECHNICIAN	OPERATOR	NONE OF ABC	INCHARGE FITTER/TECHNIC IAN	Medium
11	PC8	WHY CLEANING OF WORK AREA NEEDED	For comfortable atmosphere	For safety of work person	For avoid pollution	None of abc	Safety of work persons	medium
10	Pc7	ASSIST.SUPPORT PERSON HAVE KNOWDE OF TOOLS AND TACKLES FOR	ALLATTED WORK	REPAIRING WORK	OVERALL WORK	ALL OF THE ABC	ALL OF THE ABC	
9	PC6	WHILE HANDLING TRALLING CABLE USED PPE	GAGALE	DUST MASK	HAND GLOVES	NONE OFABC	HAND GLAVES	

			REGULAR WASHING						HARD
		PC1	&CLEANING IS			PERFORMANC			
20		8	IMPROVE THE	EFFICIENCY	LIFE	E	ALLABC	ALL ABC	MACHINE
21	MIN/ N0240	PC1	IF YOU ARE DEPLOYED TO SHIFTING OF MACHINE THEN YOU CHECK FIRST	ROUTES	SITE OF SHIFTING	RULES RELATED TO SHIFTING	ALL ABC	ALL ABC	HARD
22		PC2	THE DISTANCE OF WORKING PLACES FROM BLASTING SITE SHOULD BE MAINTAINED.	100 MTRS	200 MTRS	300 MTRS	500 MTRS	500 MTRS	HARD
22		FCZ	THE LENGTH OF TRAILLING CABLE USED WITH	100 WITKS	200 WTKS	300 WTK3	JUD IVITAS	JOU WITKS	HAND
23		PC3	EXCAVATOR IN OCM	1000 mtrs	2000mtrs	3000mtrs	300mtrs	300 mtrs	Medium
24		PC4	WHILE GUIDING THE DRILL MACHINE TO MARKED SITE POSITION WHICH IS TRUE TO FALLOW	POSITION IS VISIBLE FROM DISTENCE	MAINTAINED DISTENCE FROM MACHINE	STAND AT SAFE PLACE TO GUIDE	NONE OF ABC	STAND AT SAFE PLACE TO GUIDE	EASSY
25		PC5	WHAT FACTORS YOU OBSERVED AT SITE BE SHIFTING	GROUND STABILTY	WATER PERCULATION	ROUTE CLEARENCE	ALL AB C ARE CORRECT	ALL ABC ARE CORRECT	HARD
26		PC6	WHAT FACTORS YOU OBSERVED IN DUMPING AREA FOR SAFETY	STABILITY OF DAMPS	NO VISIBLE CRACKS	NO WATER ACCUMULATI ON OR SEPPAGES	ALL ABC ARE CORRECT	ALL ABC ARE CORRECT	HARD
27		PC7	WHAT ARE THE RULE FOR SAFE DAMPING AREA	NO PERSON SLEEPING	NO SITTING AT DAMP	NO ONE ALLOWED AT/ TO UNLOADING AREA	ALL ABC ARE CORRECT	ALL ABC ARE CORRECT	EASSY
28		PC8	IF YOU OBSERVED ANY UNUSUAL SOUND, VIBRATIONS ,LEAKAGES DURING OPERATION THEN	INFORM OPERATOR	INFORM MANAGER	REPORT ENGINEER	REPORT DIRECTOR	INFORM OPERATOR	EASSY

IF YOU ARE WORKING AS A HELPER OF DRILL OPERATOR THEN PCC9 YOU WILL HELP CHANGEING OF CLEANING OF DRILL DRILL ROD CUTTINGS MACHINES ALL ARE OF ABC CORRECT	
HELPER OF DRILL OPERATOR THEN PCC9 YOU WILL HELP CHANGEING OF CLEANING OF DRILL MAINTAINING ALL ARE	
OPERATOR THEN PCC9 YOU WILL HELP CHANGEING OF CLEANING OF DRILL MAINTAINING ALL ARE	
PCC9 YOU WILL HELP CHANGEING OF CLEANING OF DRILL MAINTAINING ALL ARE	
29 &10 DURING DRILL ROD CUTTINGS MACHINES ALL ARE OF ABC CORREC	T EASSY
HOW TO SUPPRESS	
PC1 DUST IN WORKING BY WATER BY WATER	ER MEDIUM
30 1 PLACES BY CLEANING BY BROOMING SPRYING NONE OF A B C SPRYING	i
WHAT ARE THE	
ACTIVITY NEEDED TO	
MIN/N PC12 SAFE CABIN OF CLEANING OF CLEANING OF MIRRORS CLEANING OF ALL A B C ARE ALL A B	C ARE
31 0240 & 13 OPERATOR FLOOR MATS /GLASSES DASH BOARD CORRECT CORRECT	
CHOUSE THE DRILL	
PC1 MACHINE FROM JACK	
32 4 BELOW EXCAVATOR DOZAR ROAD ROLLAR JACK HAMMERS HAMME	RS EASSY
PC1 WHAT ARE THE DIA.	
33 4 OF WAGAN DRILL? 25TO 35 mm 100mm 200mm 150mm 25 to 35	mm medium
What are the most	
important factor in	
distant	
communication Use of Proper	
34 PC16 without any aides Proper signaling Verbal Talk instrument None of ABC signalling	g Medium
TOOLS TOOLS	5 Wiediaiii
/TACALS/MATERIALS	
SHALL KEPT A	
MINIMUM DISTANCE	
FROM EDGE OF	
EXCAVATION OR 100	
35 PC17 MACHINE 100MM 10 mm 50cms 100cms 100cms	Medium
WHAT IS THE	
MIN/N GRADIENT OF THE	
36 0901 PC1 MAIN HAUL ROAD? 1IN6 1IN2 1IN 5 1IN 16 1IN16	EASSY
WHAT IS THE	
GRADIENT OF THE	
37 PC1 TEMPORARY RAMP? 1IN5 1IN10 1IN8 1IN6 1IN10	EASSY
77 FCI IEIVIFORANI NAIVIF! IIIV3 IIIV10 IIIV0 IIIV0 IIIV0	EASSI
SAFETY FUNCTIONS	
OF THE EXCAVATORS CUTOFF CUTOFF	
38 PC1 ? SWITCHES RETARDER BOTH PULL CARD SWITCHE	ES HARD

	1		1				1		
			WHAT ARE THE						
			SAFETY FUNCTION			DYNAMIC	ALL OF ABC ARE	ALL OF ABC ARE	
39		PC1	OF DAMPER ?	TURBO GUARD	BLIND MIRRORS	RETARDER	CORRECT	CORRECT	MEDIUM
40		PC2	CHOOSE PERSONAL PROTECTIVE EQUIPMENTS TO PREVENT PERSONAL INJURIES ?	MINING SHOES	GAGALES	HAND GLOVES	ALL ABC ARE CORRECT	ALL ABC ARE CORRECT	EASSY
	MIN/N 0901		WHAT PPE USED FOR RESPIRATORY		SUOTS	548 8440	DUST MASK	BUSTAMOV	5.4.CCV
41		PC2	PROTECTION	GAGALE	SHOES	EAR PLUG	DUST MASK	DUST MASK	EASSY
42		PC2	WHAT PPE USED FOR NOISE PROTECTION ?	EAR PLUG	SEAT BELT	HAND GLOVES	SHOES	EAR PLUG	EASSY
43		PC2	SEAT BELT IS USED BY	BY BLASTING CREW	SUPPORTING CREW	PUMP OPERATOR	HEMM OPERATOR	HEMM OPERATOR	EASSY
44		PC3	WHAT IS AN EXAPLE OF SAFE BEHAVIOR AT WORKING PLACES	ALWAYS USED PPE	INSIST CO WORKERS TO DO SAFE ACTIONS	NEVER USE HAZARDOUS MATERIAL	ALL ABC ARE CORRECT	ALL ABC ARE CORRECT	EASSY
45		PC3	A JACK NEVER BE USED TO SUPPORT	LOAD	LIFTED LOAD	A AND B BOTH	NONE OF ABC	A AND BABOTH	EASSY
46		PC4	MOTOR GRADER IS USED FOR	DRILLING	DIGGING	LEVELINGOF HAUL ROADS	NONE OFABC	LEVELLING OF HAUL ROADS	EASSY
47		PC5	FAILURE TO EXPLODE ENTIRE CHARGE OF AN HOLE IS	SOCKET	BLAST	DRILL HOLE	MISFIRE	MISFIRE	MEDIUM
48		PC7	CO2 GAS TYPE FIRE EXTINGHUSHERS USE TO EXTINGHUSE	CLASS A&B&C	CLASS B&C	CLASSA&C	NONE OF ABOVE	CLASS B&C	MIDIUM
49		PC7	DCP TYPE FIRE EXTINGHUSHER USED TO EXTINGHUSHE	CLASS B FIRE	CLASS C FIRE	CLASS A FIRE	A AND B BOTH	A AND B BOTH	HARD

50	PC8	WHAT BESIC STEPS YOU CAN TAKE IN EMERGENCY	DESIDE EXCUTE	CALL CHECK CARE	CHECK CALL	RECOGNISE DESIDE CALL	CALL CHECK	HARD
51	PC8	IF YOU INJURED AT WORKING PLACE THEN	REPORT & TAKE FIRST AID	WORK CONTINUOUSLY	STOP WORKING	GO HOME	REPORT & TAKE FIRST AID	eassy
52	PC9	Unstable surface will be designated bycolour flags	RED COLOUR	YELLOW	GREEN	BLUE	RED COLOUR	EASSY
53	PC10	IF ANY INCIDENT OR ACCIDENT OCCURE THEN YOU	INFORM SAFETY OFFICER	INFORM SUPERVISOR	INFORM MANAGER	INFORM ALL ABC	INFORM ALL ABC	MEDIUM
54	PC11	REPORT DAILY ACTIVITIES ABOUT EQUIPMENT IN THE	DAILY ATTENDENCE SHEET	DAILY LOG SHEET	WEEKLY LOG SHEET	OPERATION MANNUAL	DAILY LOG SHEET	HARD
55	PC5	SAFETY FUNCTION OF CRUSHER IS	PULL CARD	RETARDER	MIRROR	RERAILER	PULL CARD	HARD